



**New CONCEPT**  
QUALITY DOORS LTD.



## Lifetime Warranty Blinds Between Glass



- Blinds are sealed between safety tempered glass.
- Always transport, store and install with blinds in raised position.
- To tilt blinds, simply slide top operator.
- To raise or lower, tilt the blinds into the open position.
- Do not over tighten (max 18-20 inch/lbs).
- Limited lifetime warranty details available at: [www.RSLinc.com/marketing/energy](http://www.RSLinc.com/marketing/energy)
- Raising the blinds uses magnets. If handle becomes disengaged it is easy to reconnect. Simply slide handle to the top of track until you hear two clicks. Now magnets are reengaged & ready for use.
- Easy to clean; no dusting!
- Maintenance-free frame does not require painting or staining. If painting is desired, use primer and paint labeled 'for plastics'. Then use 2 coats of clear polyurethane. Paint thinners or similar chemicals void warranty.



### Energy Performance Rating U/SHGC

	Clear	Low-E
Half Lite	.24/.06	.21/.03
Full Lite	.30/.09	.25/.05

Ratings represent overall door performance using generic door frames and slabs. For additional test data, see [www.RSLinc.com/marketing/energy](http://www.RSLinc.com/marketing/energy).



[www.RSLinc.com](http://www.RSLinc.com)



## Lifetime Warranty on Frame & Glass



- Install with screws to inside.
- Do not over tighten (max 18-20 inch/lbs).
- Interior decorative glass is handcrafted, so bubbles and pattern variations are not defects.
- Limited lifetime warranty details available at: [www.RSLinc.com/marketing/energy](http://www.RSLinc.com/marketing/energy)
- Storm doors can cause heat damage not covered by warranty. Venting storm doors are recommended.
- Maintenance-free frame does not require painting or staining. If finishing is desired, apply 2 coats of exterior latex paint or gel stain. Then top coat with 2 coats of clear polyurethane. Paint thinners or similar chemicals void warranty.



### Energy Performance Rating U/SHGC

	Decorative w/ Caming
Half Light	.23/.16
3/4 Light	.24/.19
Full Light	.28/.24

Ratings represent overall door performance using generic door frames and slabs. For additional test data, see [www.RSLinc.com/marketing/energy](http://www.RSLinc.com/marketing/energy).



[www.RSLinc.com](http://www.RSLinc.com)